

Year	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

Alan D. Rosenthal

Background of the Invention

Semisubmersible vessels typically have a superstructure deck or decks supported by columns which are attached to hulls or pontoons which have adjustable ballast capability. By adjusting the ballast carried by the pontoons, the pontoons may be positioned at or near the surface of the water or in a submerged location below the surface of the water, while the superstructure deck remains above the surface of the water. While being moved to a location where the vessel is to be used, the pontoons typically are ballasted to permit them to ride at or near the surface of the water, facilitating transport of the vessel. After reaching the desired location, the ballast of the pontoons may be adjusted to cause the pontoons to become submerged below the surface of the water, providing improved stability and reduced motion of the vessel in rough, deep seas. The vessel may or may not be self-propelled.

2

to provide enclosed spaces for locating and storing various equipment (e.g., anchors, chains, propulsion mechanisms, etc.), and to provide a plurality of separate tanks for purposes of ballasting the vessel and storing various fluids
5 and other materials which may be required or desired during drilling or produced by the well.

The columns typically have been placed such that the vertical centerline of the columns intersects the axial centerline of the starboard or port pontoon on which the
10 column is located. In a ring pontoon semisubmersible vessel previously proposed, the four corner columns have been placed such that the vertical centerline of the columns intersects the axial centerline of the forward or aft pontoon as well.

15 Summary of the Invention

The present invention relates to improvements in ring pontoon semisubmersible vessels.

In one embodiment of the present invention, the columns are located such that the centerline of the column
20 is displaced from the axial centerline of the forward and aft sections of the ring pontoon. A vertical partition in each column lies in the same plane as, and therefore forms an extension of, the interior side of either the forward or the aft section of the pontoon ring.

25 In another embodiment of the invention, the columns also are located such that the centerline of the column is displaced from the axial centerline of the starboard and port sections of the ring pontoon.

Brief Description of the Drawings

Figures 1, 2, and 3 are the side elevation, cross section, and plan views respectively of one embodiment of the invention.

5 Figures 4A, 4B, 4C, and 4D show exemplary centerline vertical cross sections of the ring pontoon in various embodiments and at various locations along the ring pontoon.

 Figures 5, 6, and 7 are the side elevation, cross section, and plan views respectively of another embodiment
10 of the invention.

 Figures 8, 9, and 10 are the side elevation, cross section, and plan views respectively of yet another embodiment of the invention.

Description of the Preferred Embodiments

15 This invention relates to improvements to ring pontoon semisubmersible vessels.

 In a ring pontoon vessel such as is shown in Figures 1, 2, and 3, the forward, aft, starboard, and port pontoons 11, 12, 13, and 14, respectively, form a ring 10.
20 The shape of the ring is not required to be circular, and typically is either substantially square or rectangular, although other shapes (e.g., hexagonal, octagonal, etc.) are possible. The ring 10 shown in Figure 3 may be considered to be substantially rectangular, or may be considered to be
25 octagonal.

 The vertical cross section of the ring is either substantially square or rectangular. Other cross sectional shapes (e.g., octagonal, etc.) are possible. The vertical cross-section of the starboard pontoon 13 and the port
30 pontoon 14 is substantially rectangular, having curved edges. While the vertical cross section of the ring may be symmetrical, that is not required.

Moreover, the vertical cross section of the ring 10 may vary from location to location along the longitudinal axis of the ring. For example, as shown in Figure 4, the vertical cross section of the forward pontoon 11 and/or the aft pontoon 12 may be substantially different from the vertical cross section of either the starboard or port pontoons 13 and 14. Figure 4A is representative of a centerline vertical cross section for the starboard and port pontoons 13 and 14, and also may represent the centerline vertical cross section for the forward and aft pontoons 11 and 12. Alternatively, either or both of the forward and aft pontoons may have a significantly different vertical cross section. Examples of alternative centerline vertical cross sections are shown in Figures 4B, 4C, and 4D, which represent a "barge bow" cross section (Figure 4B), a raised reduced cross section (Figure 4C), and a lowered reduced cross section (Figure 4D). When a reduced cross section is selected for the design of the forward and/or aft pontoon, there will be a transition region 20 at which the cross section of the forward and/or aft pontoon transitions from one cross sectional shape to another.

Typically, the centerline vertical cross sections of the starboard and port pontoons, and the centerline vertical cross sections of the forward and aft pontoons, would be the same, although this is not required. Similarly, the centerline vertical cross sections of all of the pontoons may be the same.

As shown in Figure 3, each pontoon is subdivided by at least one vertical bulkhead 31 which is parallel to the longitudinal axis of the pontoon, and may be subdivided further by one or more vertical partitions or bulkheads 32 which are transverse such axis, into various fluid tight compartments or tanks. Similarly, each column is divided by

one or more vertical partitions or bulkheads 33 and 34 into multiple compartments or tanks. These partitions or bulkheads also contribute to the structural strength and rigidity of the pontoons and the columns.

5 Also shown in Figure 3 are four additional tanks or compartments 40 which have been formed, one at each of the interior corners of the ring 10. These additional tanks or compartments further reinforce and become part of the ring 10.

10 As shown in Figure 3, the vessel uses at least four corner columns 61, 62, 63, and 64, which are connected to the pontoon ring 10 near the forward and aft ends of the starboard and port pontoons, respectively. Additional columns, such as columns 65 and 66, also may be used if
15 desired. The columns support the superstructure deck 70, as shown in Figures 1 and 2, above the pontoon ring 10.

Additional braces 50 may extend radially inward from the ring pontoon 10 to locations on the superstructure deck 70 located inwardly of the ring pontoon 10, and serve
20 to further reinforce and strengthen the vessel.

In one embodiment of the invention, each the corner columns 61, 62, 63, and 64 are located at positions on the ring which permit at least one of the interior vertical bulkheads of such column to be in the same plane as either
25 the interior or exterior surface of the pontoon. As shown in Figure 3, vertical bulkhead 33 in each of the four corner columns lies in the same plane as the interior surface 38 of the forward pontoon or interior surface 39 of the aft pontoon. This permits the vertical bulkhead 33 to be formed
30 as an extension of the interior surface 38 of the forward pontoon or interior surface 39 of the aft pontoon.

Locating each of the four corner columns as described permits the center of each of such column to be

displaced horizontally from the axial centerline of the forward and aft pontoons, while taking advantage of the structural integrity which results from having a vertical surface of the pontoon be contiguous with and extend into one of the interior vertical bulkheads in the column. By displacing the center of the corner columns horizontally from the axial centerline of the forward and aft pontoons, movement of the superstructure deck due to wave motion is reduced.

In another embodiment of the invention shown in Figures 5, 6, and 7, the positions of the columns are displaced even more, such that an exterior vertical surface of the column lies in the same plane as the opposite surface of either the forward or aft pontoon. Thus, the most forward surface of the column 61 is in the same plane as the most aft vertical surface of the forward pontoon 11, and the most aft surface of the column 62 is in the same plane as the most forward vertical surface of the aft pontoon 12.

In the embodiment shown in Figures 5, 6, and 7, braces 50 extend from each of the corner tanks or compartments 40 to the deck of the superstructure 70.

In yet another embodiment of the invention shown in Figures 8, 9, and 10, the positions of the four corner columns have been displaced not only from the axial centerlines of the forward and aft pontoons, but also from the axial centerlines of the starboard and port pontoons. This permits even further reduction of the movement of the superstructure deck due to wave action, while retaining a very strong and rigid base structure.

What is claimed is: